



ECOLED LINEAR LED DRIVERS

Features :

- Customized Design.
- External Current Adjustment.
- 440V withstanding.
- 4KV surge protection.
- EMI/ EMC.
- Dimming.

Applications :

- Panels.
- Down Lights.
- Troffers.
- Linear Lights.
- Industrial Battens.

| Driver Model | Max Wattage | Voltage and Current | Dimensions L x W x Hmm | BIS Model No |
|-------------------|-------------|---------------------|------------------------|-------------------|
| ECI-20-PE-36-500 | 20 | 36V, 500mA | 182 x 30 x 21 | ECA30V40035A65-S |
| ECI-20-PE-48-350 | 20 | 48V, 350mA | 182 x 30 x 21 | ECA40V60020A50-S |
| ECI-40-PE-36-1000 | 40 | 36V, 1000mA | 210 x 30 x 25 | ECA30V40050A110-S |
| ECI-20-PF-48-700 | 40 | 48V, 700mA | 210 x 30 x 25 | ECA40V60030A085-S |
| ECI-40-PF-72-500 | 40 | 72V, 500mA | 210 x 30 x 25 | ECA42V75030A085-N |
| ECI-40-PG-36-1000 | 40 | 36V, 1000mA | 140 x 45 x 30 | ECA20V40060A130-S |
| ECI-40-PG-48-700 | 40 | 48V, 700mA | 140 x 45 x 30 | ECA30V55040A090-S |
| ECI-60-PH-36-1500 | 60 | 36V, 1500mA | 290 x 32 x 25 | ECA30V40120A180-S |

ECOLED illuminations Pvt Ltd.

Plot No: 188/9A, Phase -II, Charlapalli, Hyderabad-500051

Ph: +91 40 2956 4889, Email: ecoled@ecoled.co.in, www.ecoled.in.